

PLA215ST Datasheet

The PLA215ST is a specifically designed low frequency enclosure. Its effective range is from 40Hz to 200Hz making it ideal for 3/4 way applications and is ideally suited to other enclosures in our range. It is capable of delivering high impact bass and is ideally suited to small to medium size venues.

The cabinet contains two 15" drivers (one inverted) in a direct radiating configuration.

The cabinet is constructed from 18mm 13 ply Scandinavian birch and MDF internal baffles, screwed & glued with routed edges and recessed handles and plates. It is available with various finishing and hardware options.



Cabinet shown is ground stacked touring spec with steel bar handles fitted and textured paint finish. The cabinet is designed to be stacked upright or horizontal.

Spec:

Dimensions	850mm W 800mm (930mm with castors) D 590mm H
Weight	75 kg (dependent on hardware options)
Components	2 x 15"
Frequency Response	40Hz to 150Hz +/- 3db
Power Handling	1600W continuous 3200W peak
Sensitivity SPL	103dB @ 1W RMS @ 1M
Max SPL	140 dB Peak @ 1M
Crossover	Recommended 200Hz Low Pass 12dB/oct
Impedance	4Ω
Connector	Neutrik Speakon Pins 1+ 1- 2+ 2-
Finnish	Painted (colour choice) or carpet covered (black)
Grille	Steel Punched with foam front
Options	Carpet or paint finish, with or without handles for installation version.
Accessories	